



## Pneumatic truck roller Pneumatisk fordonsflyttare Pneumatisch Rollentransportgerät für LKWs

#	Article #	Order #	Pcs.	EN	SE	DE
1	V1250B	21338	1	Truck roller 25 ton	Fordonsflyttare 25 ton	Rollentransportgerät 25 Tonnen
2	V350B	21331	1	Truck roller 15 ton	Fordonsflyttare 15 ton	Rollentransportgerät 15 Tonnen



The equipment shall only be operated on flat and smooth surfaces.

Utrustningen är avsedd för användning på plana och jämna ytor.

Das Gerät darf nur auf ebenen und glatten Flächen betrieben werden.

Technical information		Teknisk information		Technische Information	
Min. wheel diameter	600 mm	Min. hjuldiameter	600 mm	Min. Raddurchmesser	600 mm
Max speed:		Max. hastighet:		Max Geschwindigkeit:	
V1250B	25 m/min	V1250B	25 m/min	V1250B	25 m/min
V350B	23 m/min	V350B	23 m/min	V350B	23 m/min
Working pressure	6 bar / 0.6 MPa	Arbetsstryck	6 bar / 0,6 MPa	Betriebsdruck:	6 bar / 0,6 MPa
Max air pressure:	8 bar / 0.8 MPa	Max. lufttryck:	8 bar / 0,8 MPa	Max. Luftdruck:	8 bar / 0,8 MPa
Capacity:		Kapacitet:		Kapazität:	
V1250B	25 tonnes	V1250B	25 ton	V1250B	25 Tonnen
V350B	15 tonnes	V350B	15 ton	V350B	15 Tonnen
Air consumption:		Luftförbrukning:		Luftverbrauch:	
V1250B	1250 l/min	V1250B	1250 l/min	V1250B	1250 l/min
V350B	650 l/min	V350B	650 l/min	V350B	650 l/min
Sound level:	85 dB (A) at 6 bar	Ljudnivå:	85 dB (A) vid 6 bar	Lautstärke:	85 dB (A) bei 6 bar
Weight:		Vikt:		Gewicht:	
V1250B	20 kg	V1250B	20 kg	V1250B	20 kg
V350B	14 kg	V350B	14 kg	V350B	14 kg
Manufacturer:	Easy Mover Rejmyre Maskin AB	Tillverkare:	Easy Mover Rejmyre Maskin AB	Hersteller:	Easy Mover Rejmyre Maskin AB