

## MEASURING RANGE

Toe	±25°
Camber	-5° ... +10°
Caster	±20°
KPI	±20°
Max. turn	60°

## MEASURING ACCURACY

Toe	±0.25 mm/m*
Camber	±3 min*
	* For each measuring head

## OPERATION

Operational time	12 h**
Charging time	1 h
Laser class	2
	** On fully charged batteries

## COMPUTER REQUIREMENTS

Supported operating systems	Windows® 10 & 11
Other software requirements	Administrator rights during installation and registration of the software.
CPU	64-bit CPU is required. Recommended: • Intel 8th generation processors (Intel i3/i5/i7/i9-7x), Core M3-7xxx, Xeon E3-xxxx, and Xeon E5-xxxx processors • AMD 8th generation processors (A Series Ax-9xxx, E-Series Ex-9xxx, FX-9xxx)
RAM	4 Gigabyte (GB) of RAM or higher recommended.
Hard disk space	20 Gigabyte (GB) of available hard disk space.
Graphics	WXGA (1366 x 768) or higher-resolution video adapter and monitor.
Input devices	Keyboard and Mouse or compatible pointing device.
Other	JOSAM Bluetooth module, article # 34389 (Note: This is included in complete measuring kits) 1 x USB-A port for software installation Internet connection required when registering license and for remote support.